DEPARTMENT OF SAFETY & PERMITS CITY OF NEW ORLEANS

PERMIT NO:	PERMIT NO: DATE:								
ADDRESS: 5120 MONTEGUT ST70126 SUBDIVISION: GENTILLY WOODS									
DISTRICT:	3RD SQUARE: 23 LOTS: 19								
COMMUNITY NUMBER	PANEL NUMBER	SUFFIX	DATE OF FIRM IND	EX	FIRM ZONE	BASE FLOOD ELE (BFE)		FREEBOAR (ADD 1FT FOR AND V ZONES OFFICE USE ONL	
225 203	0118	F	9/30/16		х	N/A	N.A.V.D	+1ft =	
MINIMUM FLOOR ELEVATION: IN ADDITION TO THE FEMA ELEVATIONS, THE FOLLOWING CONDITIONS MUST ALSO BE MET: A. TOP OF SLABS ON GRADE OR FILL MUST BE AT LEAST 36" ABOVE THE HIGHEST POINT OF CURB IN FRONT OF THE LOT OR SITE. B. PIER CONSTRUCTION: TOP OF PIERS (UNDERSIDE OF SILLS) MUST HAVE AT LEAST 18" CLEARANCE BENEATH THE STRUCTURE. IN ADDITION, THE LOWEST FLOOR MUST BE AT LEAST 36" ABOVE THE HIGHEST POINT OF CURB IN FRONT OF THE LOT OR SITE. (IF NO CURB, USE CENTERLINE OF STREET) C. ALL MECHANICAL OR PLUMBING EQUIPMENT SERVICING THE BUILDING MUST BE LOCATED AT OR ABOVE THE REQUIRED FLOOR ELEVATION. D. SLABS FOR ATTACHED GARAGES MUST BE AT THE REQUIRED FLOOR ELEVATION OR BE CONSTRUCTED OF WATER-RESISTANT MATERIALS WITH PROPER VENTING IN 2 WALLS. E. DETACHED GARAGES WITH PLUMBING MUST BE AT THE REQUIRED FLOOR ELEVATION. F. CONSTRUCTION BENCHMARK MUST BE SET AT REQUIRED MINIMUM FLOOR ELEVATION OR GREATER. (ADD 1 FOOT FOR A & V-ZONES)									
1.		CERTIFICA	ATE OF CONSTRUCT	ION B	FNCHMARK				
EXISTING HIGHEST TOP OF CURB ELEVATION6.5'N.A.V.D. EXISTING HIGHEST CENTERLINE OF STREET5.9'N.A.V.D									
ELEVATION OF CONSTRUCTION BENCHMARK:3.5'N.A.V.D. (SEE NOTE F.) REFERENCE BENCHMARK USED TO ESTABLISH CONSTRUCTION BENCHMARK: ALCO ELEVATION OF REFERENCE BENCHMARK:5.8'N.A.V.D. SIGNATURE:									
2. CERTIFICATE OF TOP OF FORM OR TOP OF PIER ELEVATION (To be submitted before pouring concrete for slab construction or framing floor for pier construction)									
AS BUILT ELEVATIONS: FORM N.A.V.D. PIER N.A.V.D.									
<u>PIER CONSTRUCTION</u> : ALL FRAMING MATERIALS BELOW THE MINIMUM FLOOR ELEVATION (B.F.E.) MUST BE CONSTRUCTED WITH WATER-RESISTANT MATERIALS AND THE FIRST FLOOR MUST BE AT OR ABOVE THE MINIMUM FLOOR ELEVATION (B.F.E.).									
V ZONES ONLY: BOTTOM OF LOWEST HORIZONTAL STRUCTURAL MEMBER N.A.V.D. (Must be submitted before framing begins) IN V ZONES, ALL ENCLOSURES BELOW THE B.F.E. MUST BE DESIGNED WITH BREAK-AWAY WALLS CONSTRUCTION.									
			UVEYOR OR CIVIL E		ER)		(SEAL	-)	
3. FILLING, GRADING, DRAINAGE, SIDEWALK AND DRIVEWAY CERTIFICATION AND AFFIDAVIT (To be submitted before Use & Occupancy Certificate can be issued)									
THIS WILL CONFIRM THAT ALL FILLING, GRADING, DRAINAGE, SIDEWALKS AND DRIVEWAYS HAVE MET THE REQUIREMENTS OF THE APPLICABLE SECTIONS OF THE CODE OF THE CITY OF NEW ORLEANS.									
OWNER:		DATE	:						
APPLICANT:		DATE	i		(NOT	ARY)			
(minimum lot slop ARE SIDEWALKS ARE DRIVEWAYS ARE RETAINING V (if yes, then on v ARE EQUIPMENT AT MINIMUM FLOO DO ATTACHED GA THAT ARE BELOW HAVE PROPER VE	ne, rear to from PROPERLY IN PROPERLY IN WALLS REQUIFWHICH SIDE SLABS, SUCH DR ELEVATION RAGES IN A-ZEMINIMUM FLOR	ont, 1 inch STALLED? STALLED? RED? RIGHT AS A/C CO V? CONES, COR ELEVA	YESNOYESNOYESNOLEFTRE MPRESSORS,YESNO	AR	YES	NO NO			
SIGNATURE:			D	ATE: _		_			

