

**solus**

Fire Features  
www.solusdecor.com

HEMI 36  
ELECTRONIC START NG & LP

Fire is beautiful and also dangerous if not handled properly. Please have a qualified gas fitter setup and install this product according to local codes.

This product has been tested and certified by Labtest Certification Inc. as being safe as long as these minimum clearances to adjacent materials are maintained.

FOR OUTDOOR USE ONLY



**NORTH AMERICA SPECIFICATIONS**

Gas type:	Natural Gas	Propane
Gas press:	3.5" - 7.0" w.c.	N/A
Electrical:	24V / 110 VAC	24V / 110 VAC
	1.5A, 60 hz	1.5A, 60 hz
BTU:	73,500	73,500

ANSI Z21.97-2014  
CSA 2.41-2014



**UK & EUROPEAN SPECIFICATIONS**

Gas type:	Natural Gas	Propane
Gas press:	G20-20 mbar	G30-30 mbar
Electrical:	240~V, 0.13A	240~V, 0.13A
	50/60 hz	50/60 hz
	0.027kW	0.027kW
Heat Out:	G20/21.5	G30/21.5

EN 509:2000  
EN 60335-1:2001



**CONCRETE SPECS**

Strength:	10,000 psi (proprietary)
Weight:	171 lbs / 78 kg

JOB / ORDER  
Name or Number:

Signature & Date:

