WORK APPROVED:

- 1. Remove existing shingle roof and install architectural grade asphalt/fiberglass roof shingles, as per attached asphalt shingle brands and colors, approved 11/11/2022.
- 2. Remove and salvage existing English-V ridge tiles for reinstallation. Reinstall all salvaged ridge tiles.
- 3. Repair/replace plywood decking, sheathing, and felt paper, as needed. Overall pitch and height of roof to match existing.
- 4. Remove existing rear TPO roofing and install new TPO roofing to match existing.
- 5. Remove existing R-panel roofing at rear yard covering and install new R-panel roofing to match existing.
- 6. All repair/replace shall match existing in material, exposure, dimension, size, operation, configuration, and type, unless otherwise specified.
- 7. All changes and additional work must be approved by the HDLC.
- 8. Contact HDLC Inspector Alex Nassar at (504)658-7045 or anassar@nola.gov for final inspection.

NOT VALID UNLESS POSTED ON SITE

By posting this notice, the owner of the property certifies that they understand all work described above, and acknowledge that they are legally responsible for ensuring that all work performed has been approved prior to execution and is completed in accordance with approvals obtained. ••• For questions regarding this approval or to schedule a final inspection call the number below ••• THIS FORM MUST REMAIN POSTED UNTIL WORK IS CERTIFIED AS COMPLIANT BY HDLC STAFF

1300 Perdido Street, Room 7W03 • New Orleans • LA • 70112 • (504) 658-7040 • www.nola.gov/hdlc SOLO EL TRABAJO DESCRITO ANTERIORMENTE PUEDE REALIZARSE LEGALMENTE EN ESTE EDIFICIO